

FEATURES

- · Industrial strength degreaser floats away grease, oil, dirt, soap scum, light carbon, and other grime
- · Variable dilution rate from 1-12 ounces per gallon
- All-purpose, all-surface use wherever heavy soil is found
- Classified non-hazardous by DOT
- Ideal for use in federally inspected meat and poultry plants

GENERAL DILUTIONS

Heavy Cleaning 1 to 20 water Light Cleaning 1 to 60 water General Cleaning 1 to 40 water

SPECIFIC DILUTIONS

Air Filters	1 to 4 water
Whitewall Tires	1 to 1 water
Conveyors	1 to 10 water
Concrete Floors	1 to 20 water
Engines, Machinery	1 to 2 water
Damp Mopping	1 to 60 water
Kitchens (ovens)	1 to 4 water
Walls, Ceilings	1 to 20 water
Metal Surfaces	1 to 10 water

Machine Sumps	1 to 10 water
Printing Plants	1 to 10 water
Plastics	1 to 40 water
Scrubbing Machines	1 to 20 water
Shower Stalls	1 to 10 water
Stainless & Aluminum	1 to 20 water
Swimming Pools	1 to 10 water
Terrazzo	1 to 30 water
Air Conditioning (ducts, grills)	1 to 20 water
Exhausts, Flues	1 to 2 water

PROPERTIES

TypeButyl Degreaser
FormClear Liquid
OdorPine Detergent
ColorPurple
Weight per Gallon 8.73 lbs.
pH12.3 - 13.0
pH 1%
Storage StabilityMin. 1 Year
Freeze/ThawPasses 3 Cycles
Foam HeightMedium High
Flash Point (c.c.)None
Actives>15%
Phosphate (%P) 0.9

Properties are typical and subject to usual manufacturing tolerances.

> Scan QR code for access to the Safety Data Sheet.

